

RECEIVED  
CENTRAL FAX CENTER

AUG 15 2006

PATENT APPLICATION  
DOCKET NO.: 200315309-1

LISTING OF THE CLAIMS

Pursuant to 37 C.F.R. §1.121, provided below is a listing of the pending claims.

1. (Original) A printed circuit board (PCB) substrate, comprising:

a first dielectric material associated with a first current return layer;

a second dielectric material associated with a second current return layer;

a signal path layer interposed between said first dielectric material and said second dielectric material; and

an adhesive layer interposed between said first dielectric material and said second dielectric material, said adhesive layer being substantially coplanar relative to said signal path layer.

PATENT APPLICATION  
DOCKET NO.: 200315309-1

2. (Original) The PCB substrate as recited in claim 1, wherein said adhesive layer is comprised of a material operable to substantially reduce attenuation due to an electrical coupling effect between a pair of signal traces disposed in said signal path layer.

3. (Original) The PCB substrate as recited in claim 2, wherein said adhesive layer has a lower loss tangent than said first dielectric material.

4. (Original) The PCB substrate as recited in claim 2, wherein said adhesive layer has a higher glass transition point ( $T_g$ ) than said first dielectric material.

5. (Original) The PCB substrate as recited in claim 2, wherein said adhesive layer comprises a dielectric material selected from the group consisting of a two-sided adhesive tape, an adhesive film having a copper foil, an epoxy adhesive sheet, and an expanded polytetrafluoroethylene (ePTFE).

PATENT APPLICATION  
DOCKET NO.: 200315309-1

6. (Original) The PCB substrate as recited in claim 2, wherein said pair of signal traces are electrically coupled in a differential mode.

7. (Original) The PCB substrate as recited in claim 6, wherein said signal path layer further comprises at least one pair of signal traces electrically coupled in a common mode.

8. (Original) The PCB substrate as recited in claim 2, wherein said first dielectric material comprises a material selected from the group consisting of FR-4 material, pre-preg material, core material, and B-stage substrate material.

Claims 9-15. (Canceled)

PATENT APPLICATION  
DOCKET NO.: 200315309-1

16. (Original) A method for constructing a printed circuit board (PCB) substrate, comprising:

providing a first dielectric material associated with a first current return layer;

providing a second dielectric material associated with a second current return layer;

providing a signal path layer interposed between said first dielectric material and said second dielectric material; and

providing an adhesive layer interposed between said first dielectric material and said second dielectric material, said adhesive layer being substantially coplanar relative to said signal path layer.

PATENT APPLICATION  
DOCKET NO.: 200315309-1

17. (Original) The method as recited in claim 16, further comprising selecting said adhesive layer to include a material operating to substantially reduce attenuation due to an electrical coupling effect between a pair of signal traces disposed in said signal path layer.

18. (Original) The method as recited in claim 17, further comprising selecting said adhesive layer to include a material having a lower loss tangent than said first dielectric material.

19. (Original) The method as recited in claim 17, further comprising selecting said adhesive layer to include a material having a higher glass transition point ( $T_g$ ) than said first dielectric material.

PATENT APPLICATION  
DOCKET NO.: 200315309-1

20. (Original) The method as recited in claim 17, further comprising curing a layer of said PCB substrate, said layer selected from the group consisting of said first dielectric material, said second dielectric material, and said adhesive layer.

Claims 21-25. (Canceled)